

CR 1852MT



SPECIFICATIONS

Overall length	18' (5.5 m)
Beam	"75" (191 cm)
Bottom width	"52" (132 cm)
Side depth	"21" (53 cm)
# of ribs	10
Weight	475# (215 kg)
Max. weight capacity	1375# (624 kg)
Max. people capacity	6
Max. HP capacity	45
Hull gauge	0.072"
Transom	20" (51 cm)
Bench seats	3
Bottom	Flat
Bow shape	Modified-V



CR 1852MT

COLORS

Base

- › Olive Drab
- › Gray

STANDARD FEATURES

Construction/Quality/Safety

- › Warranty "Lifetime + 3" Protection Plan
- › Bow eye (stainless steel)
- › Center seat w/ gravity fed livewell
- › Drain plug
- › Formed transom corner caps
- › Formed in spray rails
- › Formed in keels
- › Oar lock sockets
- › Transom handles (2)

OPTIONS

- › Aluminum console (dealer installed)
- › Trolling motor mount

TRAILER OPTIONS

- › Karvan powdercoated bunk trailer (LB-1800-60-ST)
- › Karvan galvanized bunk trailer (LB-1800-60-ST-Galvanized)
- › Exchange Vinyl Bunk Covers for Carpeted Bunk Covers
- › Spare Silver Tire w/ Powdercoated Bracket
- › Spare Galvanized Tire w/ Galvanized Bracket
- › Ratchet tie-downs